

Two-axis Joystick Motion Controller, JMC-2-03

Two-axis Pre-wired Joystick with 3 Speed Selection Keys, PWM and Direction Signal Outputs per Axis
25-pin DB-25, Male Connector
Cable Length = 5.5 ft (168 cm)

PIN	NAME	DESCRIPTION
1		Not Connected
2		Not Connected
3		Not Connected
4		Not Connected
5		Not Connected
6		Not Connected
7	DIR-X	X-axis Direction Signal Output
8	PWM-X	X-axis PWM Signal Output
9	ENA-X	X-axis Enable Signal Output
10	DIR-Y	Y-axis Direction Signal Output
11	PWM-Y	Y-axis PWM Signal Output
12	ENA-Y	Y-axis Enable Signal Output
13		Not Connected
14		Not Connected
15		Not Connected
16		Not Connected
17	GND	System Ground
18		Not Connected
19	+5 VDC	+5 VDC Input
20		Not Connected
21		Not Connected
22		Not Connected
23		Not Connected
24		Not Connected
25		Not Connected



Optimal Engineering Systems, Inc.
6901 Woodley Avenue
Van Nuys, California 91406
U.S.A.

Phone (818) 222-9200
FAX (818) 436-0446
E-mail oes@oesincorp.com
www.oesincorp.com